

PUN 12X8 SVART



Polyuretan slang 12 x 8 mm, svart

Betyg: Inte betygsatt ännu

Pris

Pris 40,25 kr

Pris utan moms 32,20 kr

Rabatt

Momsbelopp 8,05 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

Hose Ø outside x inside [mm] 12 x 8

colour black

Operating pressure [bar] 11

Min. bend radius [mm] 40

Note RoHS-compliant

Weight 90 g / m

Further information

Packing unit 50

Customs duty number: 39173900

Description

Advantages:

-small bend radius due to being particularly flexible, -very good low temperature flexibility and reset characteristics, -kink and abrasion resistant, -resistant to aliphatic hydrocarbons and most lubricants, -ageing resistance in oxygen, -drag line compatible (min. bend radius corresponds to 10 x outer diameter)

Material:

Polyester polyurethane

PUN polyuretanrör utv tolerans: PUN 12X8 SVART

Temperature range:

-35°C to max. +60°C

Shore hardness:

97 A

Roll length:

50 m

Reference values for the pressure utilisation under temperature loading:

to +20°C: 100%, +30°C: 80%, +40°C: 68%, +50°C: 58%, +60°C: 50%

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.