OR 25



ELLER ventil M 5, precisionstyp

Betyg: Inte betygsatt ännu
Pris
Pris 234,89 kr

Pris utan moms 187,91 kr

Rabatt

Momsbelopp 46,98 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

Version precision version

Connection M 5

Nominal width [mm] 3,2

flow [l/min] 160

Note RoHs-compliant

Weight 26 g / pc.

Further information

GTIN 4050571536244

Customs duty number: 84812090

Description

Materials:

Body: anodized aluminium, internal parts: brass and stainless steel (standard design: brass and plastic), seals: NBR

ELLER (OR) ventiler: OR 25

Temperature range:

-10°C to max. +70°C (Standard design: max. +60°C)

Media:

oiled and unoiled filtered compressed air

Operating pressure:

-0.95 - 10 bar (Standard design: 2 - 10 bar)

Function:

A signal appears at outlet A, only if on inlet X or Y there is a signal. If signals are positioned at both inlets, then the higher pressure will reach outlet A. The ODER member has no venting as a passive element. After deleting both input signals ventilation occurs via the upstream signal members.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.