

KDGI 18 NW5 MSV



Snabbkoppling (NW5) G 1/8" inv gänga, nickel-plätterad mässing

Betyg: Inte betygsatt ännu

Pris

Pris 118,03 kr

Pris utan moms 94,42 kr

Rabatt

Momsbelopp 23,61 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

Material Nickel-plated brass

Thread internal G 1/8"

Can be used for plug shut-off on both sides no

Version Standard

Temperature range [°C] -20 to +100

Further information on KDGI18NW5MSV

Weight 32 g / Pcs

GTIN 4050571396411

Customs duty number 84812090

RoHS compliant Yes

Description - Coupling socket (NW5) G 1/8"(Female thread), Nickel-plated brass

Materials:

Housing: Brass, nickel-plated brass, steel hardened or 1.4305, seal: NBR (stainless steel: FKM)

Temperature range:

Snabbkoppling DN 5, inv gänga: KDGI 18 NW5 MSV

-20°C to max. +100°C (Stainless steel: -15°C to max. +200°C)

Operating pressure:

-0,95 bis 35 bar

Flow*:

560 l/min (option -BA: 360 l/min)

Note:

Coupling plugs with valve for double-sided shut off (-BA) can only be used with the special coupling sockets (-BA) provided for them.

Compatible with**:

Rectus (21, 90), Camozzi, EWO, KANI, Festo (KD3KKS), IMI-Norgren (233), Aventics (CP1-NW 5)

Optional:

Body made from 1.4404-ES4A, usable for plug shut-off on both sides -BA, NPT thread -NPT, red sliding sleeve -RO, green sliding sleeve -GR, blue sliding sleeve -BL, black sliding sleeve -SCH

*6 bar input pressure, 0,5 bar pressure difference

**Names and designations are partly trademarks of the manufacturers entered.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.