GE 4 LLR MSV



Rak skärringskoppling. 4 LL-R 1/8", nickelplätterad mässing

Betyg: Inte betygsatt ännu
Pris
Pris 29,90 kr

Pris utan moms 23,92 kr

Rabatt

Momsbelopp 5,98 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

Model series very light model series

Tube Ø outer [mm] 4 LL

Screw-in thread R 1/8"

Operating pressure with hard copper tube [bar] 100

Temperature range [°C] -60 to +300

Further information on GE4LLRMSV

Weight 13 g / Pcs

GTIN 4050571322564

Customs duty number 74122000

Description - Straight cutting ring fitt. 4 LL-R 1/8", nickel-plated brass

Materials:

Body: nickel-plated brass, cutting ring: brass

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.