G 6 LL MSV



Rak skarv skärring fitting 6 LL, nickelplätterad mässing

Betyg: Inte betygsatt ännu
Pris
Pris 51,61 kr

Pris utan moms 41,29 kr

Rabatt

Momsbelopp 10,32 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

Model series very light model series

Tube Ø outer [mm] 6 LL

Union nut thread M 10 x 1

Operating pressure with hard copper tube [bar] 100

Temperature range [°C] -60 to +300

Further information on G6LLMSV

Weight 22 g / Pcs

GTIN 4050571312657

Customs duty number 74122000

RoHS compliant Yes

Description - Straight cutting ring fitting 6 LL, nickel-plated brass

Materials:

Body: nickel-plated brass, cutting ring: brass

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.